

Model 80-21EX - Explosion Proof Chest Freezer



Standard Explosion Proof 21 cu. ft. Freezer

Class 1, Division 1—Group C & D

Exterior Dimensions	47"H x 91"W x 36.5"D <small>Includes Handle and Hinges</small>	
Interior Dimensions	32"H x 60"W x 20"D	
Temperature Range	-45C /-50F to -80C /-112F	
Capacity	21 cubic foot	
Insulation	Urethane Foam	
Door	Key Locking	
Casters	3" Locking and Non-Locking	
Temperature Controller	Analog Dial	
<u>Refrigeration</u>		
Compressor - High stage	3/4 hp	
Compressor - Low stage	3/4 hp	
Low Stage Refrigerant	R-508B	
High Stage Refrigerant	R-134A	
Voltage	230/60/1	230/50/1
Refrigerant Control	Capillary Tube	
Evaporator	Cold Wall	
Defrost	Manual	
Running Amps	8 amps (230v)	

Versatile Design

Standard models and custom designs.

Comfortable Access

Low-profile design. Controls are conveniently mounted on the front of an end rack for easy access.

Safety & Easy Access

Counter-balanced lid with magnetic gasket. Brushed aluminum and thermoplastic tubular handle with separate Keyed Hasp Lock. Sub-Lids are added for additional protection of content.

Sturdy Construction

Outer cabinet is welded steel with textured powder coat finish. Interior compartment is welded steel with a smooth white powder coat finish.

CFC Free

All products are manufactured using CFC-free, non-toxic, non-combustible and non-ozone depleting refrigerant. Compressors are permanently lubricated and hermetically sealed.

Safe and Economical


Freezers are manufactured using environmentally safe urethane foam insulation

Casters

3" Solid Polyolefin Wheel (2 Locking and 2 Non-Locking)

Customize to Meet Your Specifications

- Access Ports (1", 2" or 4" are available)
- Stainless Steel Interior and/ or Exterior



SciencTemp™

3565 S. Adrian Hwy

Adrian, MI 49221

Ph. 517-263-6020 / Fax 517-263-5492

Toll Free 1-800-968-2653

Website: www.scientemp.com

