

Model 40-21 Chest Freezer



Standard 21 cu. ft. Freezer

Exterior Dimensions	47"H x 85"W x 36.5"D <small>includes Handle & Hinge</small>	
Interior Dimensions	32"H x 60"W x 20"D	
Temperature Range	0C /32F to -40C /-40F	
Capacity	21 cubic foot	
Insulation	Urethane Foam	
Door	Key Locking	
Casters	3" Non-Locking (Locking are available)	
Temperature Controller	Digital Display	
Alarm	Visual and Audible	
<u>Refrigeration</u>		
Compressor - High stage	3/4 hp	
Compressor - Low stage	(None)	
Refrigerant	R-404A	
Voltage	230/60/1	230/50/1
Refrigerant Control	Capillary Tube	
Evaporator	Cold Wall	
Defrost	Manual	
Running Amps	4 amps (230v)	

Versatile Design

Standard models and custom designs.

Comfortable Access

Low-profile design. Controls are conveniently mounted on the front of an end rack for easy access.

Safety & Easy Access

Counter-balanced lid with magnetic gasket. Brushed aluminum and thermoplastic tubular handle with separate Keyed Hasp Lock. Sub-Lids are added for additional protection of content.

Standard Visual/Audible Alarm

Alarm monitoring system indicates power-on and displays visual/ audible warning of rise in temperature and/or power failure.



Sturdy Construction

Outer cabinet is welded steel with textured powder coat finish. Interior compartment is welded steel with a smooth white powder coat finish.

CFC Free


All products are manufactured using CFC-free, non-toxic, non-combustible and non-ozone depleting refrigerant. Compressors are permanently lubricated and hermetically sealed.

Safe and Economical

Freezers are manufactured using environmentally safe urethane foam insulation

Casters

Non-Locking heavy duty swivel type. (Locking casters are available upon request)



ScienTemp™

3565 S. Adrian Hwy

Adrian, MI 49221

Ph. 517-263-6020 / Fax 517-263-5492

Toll Free 1-800-968-2653

Website: www.scientemp.com

Customize to Meet Your Specifications

- Access Ports (1", 2" or 4" are available)
- Ramp/Soak Control
- CO2 and LN2 Back-Up Systems
- Stainless Steel Interior and/ or Exterior
- Explosion Proofing
- Observation Window
- Internal Heater and Internal Fan

Optional Accessories

- * 6" Temperature Chart Recorder - Records freezer temperature for up to 7 days.
- * Automatic Voice Pager Dialer - In the event of power failure or temperature rise, the AD-2000 will instantly deliver voice or pager message to any number. Interfaces with Alarm Panel or Stand Alone Operation. ~Can program up to 8 phone numbers.
- * Cryo-Gloves - Designed to provide protection when working with ultra cold temperatures.
- * CALgrafix Software - Features logging, charting, alarm indication, networking and configuration when connected to a Windows based user interface.

