



# ScienTemp™

## Low Temperature Freezer



**Versatile Design**—Standard Models or we can custom design one that meets your needs

**Safety & Easy Access** - Counter-balanced lid with magnetic gasket. Brushed aluminum and thermoplastic tubular handle with separate Keyed Hasp Lock. Inner Styrofoam Sub-lids are included for additional

**Safe & Economical Insulation**— Our freezers are insulated using environmentally safe PFAS-free Ecofoam Polyurethane Foam.

**CFC Free Refrigerant** - All products are manufactured using CFC-free, non-toxic, non-combustible and non-ozone depleting refrigerant. Compressors are permanently lubricated and hermetically sealed for easy maintenance.

**Sturdy Construction** - Cabinets are welded steel with a textured exterior / smooth interior powdercoat finish.

**Comfortable Access** - Low-profile design. Controls are conveniently mounted on the front of an end rack for easy access

**Casters** - Locking 3" heavy duty swivel type casters

### Model 40-21EX

Exterior Dimensions	47"H x 85"W x 36.5"D
Interior Dimensions	32"H x 60"W x 20"D
Temperature Range	0°C to -40°C / 32°F to -40°F
Capacity	21 cubic feet
Insulation	Polyurethane
Door	Keyed Hasp Lock
Casters	(4) 3" Locking
Temperature Controller	Analog Dial

\*\*Exterior height includes casters  
\*\*Depth measurement includes hinges and handle.

### Refrigeration

Compressor	1 hp
Refrigerant	R-452A
Voltage Options	208/60/1 - 230/60/1
Refrigerant Control	Capillary Tube
Evaporator	Cold Wall
Defrost	Manual
Air Circulation	Gravity
Running Amps	6 amps (208-230V)

### Optional Accessories

- Access Ports (1", 2" or 4" are available)
- Stainless Steel Interior and / or Exterior

ScienTemp Corporation 3565 S. Adrian Hwy Adrian, MI 49221 Ph: 517-263-6020

[www.scientemp.com](http://www.scientemp.com)

January 2026