

# Model 40-12 Chest Freezer



Standard 12 cu. ft. Freezer

Exterior Dimensions	49"H x 60"W x 28"D
Interior Dimensions	25"H x 49"W x 17"D
Temperature Range	0C /32F to -40 /-40F
Capacity	12 cubic foot
Insulation	High Density Fiberglass
Door	Key Locking
Casters	3" Non-Locking (Locking are available)
Temperature Controller	Digital Display
Alarm	Visual and Audible
<b>Refrigeration</b>	
Compressor - High stage	1/3 + hp
Compressor - Low stage	(None)
Refrigerant	R-404A
Voltage	115/60/1 230/60/1 230/50/1
Refrigerant Control	Capillary Tube
Evaporator	Cold Wall
Defrost	Manual
Running Amps	8 amps (115v) 4 amps (230v)

## Versatile Design

Standard models and custom designs.

## Comfortable Access

Low-profile design with toe space. Controls are conveniently mounted in front recessed instrument panel.

## Safety & Easy Access

Counter-balanced lid with magnetic gasket. Brushed aluminum and thermo-plastic tubular handle with separate Keyed Hasp Lock. Sub-Lids are added for additional protection of content.

## Standard Visual/Audible Alarm

Alarm monitoring system indicates power-on and displays visual/ audible warning of rise in temperature and/or power failure.

## Sturdy Construction

Outer cabinet is welded steel with textured powder coat finish. Interior compartment is welded steel with a smooth white powder coat finish.



## CFC Free

All products are manufactured using CFC-free, non-toxic, non-combustible and non-ozone depleting refrigerant. Compressors are permanently lubricated and hermetically sealed.

## Convenient Storage


Rack Systems available or customized systems to your specification.

## Safe and Economical

Freezers are manufactured using environmentally safe high-density, non settling fiber glass insulation.

## Casters

Non-Locking heavy duty (recessed) swivel type. (Locking casters are available upon request)



# ScienTemp™

3565 S. Adrian Hwy

Adrian, MI 49221

Ph. 517-263-6020 / Fax 517-263-5492

Toll Free 1-800-968-2653

Website: [www.scientemp.com](http://www.scientemp.com)

## Customize to Meet Your Specifications

- Access Ports (1" , 2" or 4" are available)
- Ramp/Soak Control
- CO2 and LN2 Back-Up Systems
- Stainless Steel Interior and/ or Exterior
- Explosion Proofing
- Observation Window
- Internal Heater and Internal Fan

## Optional Accessories

- \* 6" Temperature Chart Recorder - Records freezer temperature for up to 7 days.
- \* Automatic Voice Pager Dialer - In the event of power failure or temperature rise, the AD-2000 will instantly deliver voice or pager message to any number. Interfaces with Alarm Panel or Stand Alone Operation.  
~~Can program up to 8 phone numbers
- \* Cryo-Gloves - Designed to provide protection when working with ultra cold temperatures.
- \* CALgrafix Software - Features logging, charting, alarm indication, networking and configuration when connected to a Windows based user interface.

